Portable Autoclave LX102POA

Email: info@labdex.com **website:** www.labdex.com

Description

Portable autoclave LX102POA is an advanced steam sterilizer and a portable N class unit with a capacity of 24 L and a sterilizing temperature of 126 °C. It can inactive harmful bacteria, HIV, HBV, Mad cow viruses, and Bacillus, viruses and spores. An Electric or LPG heated top loading high-pressure steam sterilizing unit and a dual scale pressure gauge indicator.

Specifications

Volume of Chamber	24 L (280 x 390 mm)
Working temperature	126 ℃
Heating mode	Electrically / LPG heated
Working pressure	0.14 ~ 0.16 Mpa
Max safety pressure	0.165 Mpa
Heat average	≤ ± 1℃
Temp adjustment	105 ~ 126 ℃
Power	AC 220 V / 50 Hz / 2 KW
Overall Dimension	410 × 410 × 550 mm
Net Weight	15 Kg
Gross Weight	17 Kg

Features

- Sterilizing Temperature 126 °C
- Inner and outer Chamber formation by stainless steel
- Self-Inflating leak proof chamber
- Electric or LPG heated
- Dual scale pressure gauge indicator
- Safe and reliable

Applications

- Used in Medical, Research Institutions, Laboratory, Drinking Water Plant, Food industry, Hospital, Agriculture, Hospital, Scientific Research.

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.
Email: info@labdex.com | Website: www.labdex.com